

## Equivalence

```
expect(actual).to eq(expected) # actual == expected
expect(actual).to eql(expected) # actual.eql?(expected)
expect(actual).not_to eql(not_expected)
```

## Identity

```
expect(actual).to be(expected) # actual.equal?(expected)
expect(actual).to equal(expected) # actual.equal?(expected)
```

## Comparisons

```
expect(actual).to be > expected
expect(actual).to be >= expected
expect(actual).to be <= expected
expect(actual).to be < expected
expect(actual).to be_within(delta).of(expected)
```

## Regular expressions

```
expect(actual).to match(/expression/)
```

## Truthiness

```
expect(actual).to be_truthy # actual not nil or false
expect(actual).to be true # actual == true
expect(actual).to be_falsy # actual is falsy (nil or false)
expect(actual).to be false # actual == false
expect(actual).to be_nil # actual is nil
expect(actual).to_not be_nil # actual is not nil
```

## Types/classes

```
expect(actual).to be_an_instance_of(expected) # actual.class == expected
expect(actual).to be_a(expected) # actual.kind_of?(expected)
expect(actual).to be_an(expected) # an alias for be_a
```

## Yielding

```
expect { |b| 5.tap(&b) }.to yield_control # passes regardless of yielded args
expect { |b| yield_if_true(true, &b) }.to yield_with_no_args # no args yielded
expect { |b| 5.tap(&b) }.to yield_with_args(5)
expect { |b| 5.tap(&b) }.to yield_with_args(Fixnum)
expect { |b| "a string".tap(&b) }.to yield_with_args(/str/)
expect { |b| [1, 2, 3].each(&b) }.to yield_successive_args(1, 2, 3)
expect { |b| {:a=>1}.each(&b) }.to yield_successive_args([:a, 1])
```

## Collection membership

```
expect(actual).to include(expected)
expect(actual).to start_with(expected)
expect(actual).to end_with(expected)
expect(actual).to match_array(expected_array)
```

## Ranges (Ruby >= 1.9 only)

```
expect(1..10).to cover(3)
```

## Expecting errors

```
expect { ... }.to raise_error
expect { ... }.to raise_error(ErrorClass)
expect { ... }.to raise_error("message")
expect { ... }.to raise_error(ErrorClass, "message")
```

## Expecting throws

```
expect { ... }.to throw_symbol
expect { ... }.to throw_symbol(:symbol)
expect { ... }.to throw_symbol(:symbol, 'value')
```

## Predicate matchers

```
expect(actual).to be_xxx # passes if actual.xxx?
expect(actual).to have_xxx(:arg) # passes if actual.has_xxx?(:arg)
```

## Examples

```
expect([1, 2, 3]).to include(1, 2)
expect([1, 2, 3]).to start_with(1, 2)
expect([1, 2, 3]).to end_with(2, 3)
expect({:a => 'b'}).to include(:a => 'b')
expect("this string").to include("is str")
expect("this string").to start_with("this")
expect("this string").to end_with("ring")
expect("s").to start_with("a").and end_with("b")
expect([1, 2, 3]).to match_array([3, 2, 1])
expect { k += 1 }.to change { k }.by(1)
expect { s = "barn" }.to change { s }
  .from( a_string_matching(/foo/) )
  .to( a_string_matching(/bar/) )
```

**RSpec Expectations**, v3.5, July 1, '16 (00c895)

<https://github.com/rspec/rspec-expectations>

